



# *i-Series is Smarter Working*



## OPTIONS

**1 MEDIA INPUT**  
Paper tray  
PF-P26



**2 MEDIA OUTPUT**  
Convenience stapler  
EH-T592

**LEGEND**

- Option
- Mandatory option
- This option can only be installed with the respective option above it

## FINISHING FUNCTIONALITIES



Duplex



Corner  
Stapling  
(offline)

## DESCRIPTION

### MEDIA INPUT

PF-P26 Paper tray	250 sheets, A4, 60-176 g/m <sup>2</sup>
-------------------	---

### MEDIA OUTPUT

EH-T592 Convenience stapler	Convenient stapling of up to 50 sheets per set
-----------------------------	--

## TECHNICAL SPECIFICATIONS

### SYSTEM SPECIFICATIONS

System speed A4	Up to 31/31 ppm (mono/colour)
Autoduplex speed A4	Up to 19/19 ppm (mono/colour)
1st page out time A4	10.0/11.0 sec. (mono/colour)
Warm-up time	Approx. 35 sec. (mono/colour) <sup>1</sup>
Imaging technology	LED
Toner technology	Polymerized Toner
Panel size/resolution	2.8" / 320 x 240
System memory	512 MB (standard/max)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n
Network protocols	TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP; HTTP(S); Bonjour
Automatic document feeder	Up to 50 originals; A5-A4; 60-105 g/m <sup>2</sup> ; Dualscan ADF
Printable paper size	A6-A4; customized paper sizes
Printable paper weight	60-176 g/m <sup>2</sup>
Paper input capacity	300 sheets / 550 sheets (standard/max)
Manual bypass	50 sheets; A6-A4; custom sizes; 60-176 g/m <sup>2</sup>
Finishing modes (optional)	Group; Sort; Staple (offline)
Automatic duplexing	A5-A4; 60-176 g/m <sup>2</sup>
Output capacity	Up to 150 sheets
Duty cycle (monthly)	Rec. 1,600 pages; Max. <sup>2</sup> 62,000 pages
Toner lifetime	Black up to 6,000 pages CMY up to 4,000 pages
Imaging unit lifetime	CMYK up to 50,000 pages (imaging unit)
Power consumption	220-240 V / 50/60 Hz; Less than 1.12 kW
System dimension (W x D x H)	410 x 430 x 366 mm (without options)
System weight	Approx. 21.2 kg (without options)

### PRINTER SPECIFICATIONS

Print resolution	2400 x 600 dpi
Page description language	GDI; PCL 6 (XL3.0); PCL 5c; PostScript 3
Operating systems	Windows 8.1 (32/64); Windows 10 (32/64); Windows 11; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Windows Server 2022; macOS 10.12 or later
Printer fonts	94 PCL Latin; 93 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS); Mopria (Android); WiFi Direct

### SCANNER SPECIFICATIONS

Scan speed	Up to 30/16 ipm in simplex (mono/colour) Up to 45/22 ipm in duplex (mono/colour)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail; Scan-to-SMB; Scan-to-FTP; TWAIN scan; WIA scan
File formats	JPEG; TIFF; PDF
Scan destinations	120 destinations

### COPIER SPECIFICATIONS

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-99
Original format	Max. A4
Magnification	25-400% in 1.0% steps; Auto-zooming

### FAX SPECIFICATION

Fax standard	Super G3
Fax transmission	Analogue
Fax resolution	Up to 400 x 400 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	120 destinations

### SYSTEM FEATURES

Security	IP filtering and port blocking; SSL3 and TLS1.1/1.2/1.3 network communication; IEEE 802.1x support; User authentication; Secure print; Kerberos; Confidential fax
Accounting	Up to 50 user accounts

<sup>1</sup> Warm-up time may vary depending on the operating environment and usage

<sup>2</sup> If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

- All specifications refer to A4-size paper of 80 g/m<sup>2</sup> quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- DEVELOP and ineo are registered trademarks/product titles owned by Konica Minolta Business Solutions Europe GmbH.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

